

ML620 OPEN GEAR OIL

PRODUCT INFORMATION

A semi-synthetic lubricating oil, formulated from highly refined base oils and special additives, providing high viscosity and excellent adhesion, together with anti-wear and extreme pressure characteristics.

Beneficial Qualities

- Reduces friction, heat and wear.
 Increases gear and bushing life. Lower maintenance costs
- Reduces energy consumption and operating costs
- Excellent water resistance. Will not wash off metal surfaces. Reduces rust and corrosion
- Up to 80% less lubricant consumption.
 More economical in use. Lower lube disposal costs. Saves money
- Free of heavy metals and chlorine derivatives
- · Capacity to support heavy loads
- · Protection against wear
- · High adhesiveness/tackiness
- Does not cause staining / corrosion of yellow metals (copper and alloys)
- High Viscosity Index: maintains an adequate viscosity at high temperatures



Typical Applications

 Lubrication of open gears and large bronze bushings in many diverse industries, such as: sugar, mining, cement and paper.



Technical Details

	ASTM Test	Unit	Result
Appearance			Viscous, homogeneous, light brown liquid
Relative Density		gr/cm3	0.892
Kinematic Viscosity @ 40°C	D-445	cSt	20,000
Kinematic Viscosity @ 100°C	D-445	cSt	1.180
Flash Point	сос	°C	>180
Viscosity Index	D-2270	Typical	278
Copper Corrosion, 3 hours @ 100 °C	D-130		1b max
EP 4 Ball Test – Weld Load	D-2783	kgf	620
Pour Point	D-97	°C	- 8

Product Manufactured in Argentina under an ISO 9001 and ISO 14001 Certified Quality & Environmental Management System

DISCLAIMER NOTICE:

MAK LUBES International Ltd does not guarantee that the information about the product is complete or accurate in all respects.

MAK LUBES International Ltd does not warrant that the product is suitable for your specific use of the product.

MAK LUBES International Ltd shall not be liable for any consequential loss, incidental loss, damages resulting from misuse or sale of the product.



+44 (0) 118 930 4321



sales@mak-global.org



mak-lubes.org